

BLANKANA F

TECHNICKÝ POPIS

Základní materiál :	termoplast vyztužený tkaninou
Projekční strana :	matně bílá
Zadní strana :	černá
Tloušťka :	0,35 mm
Hmotnost :	450 g/m ²
Šíře role :	320 cm
Svařitelný :	ne
Omyvatelný :	ano
Hořlavost :	B2 dle DIN 4102 část 1
Reflexní skupina :	D (difuzní)
Použití :	přední projekce
Neprůsvitnost :	>95%
Gain :	1,1
Pozorovací úhel :	+/- 60°
Vhodné pro rozlišení :	2K

VLASTNOSTI

- široký pozorovací úhel, projekční světlo se odráží do všech směrů
- přirozené podání barev
- světlo nepropustná černá zadní strana (>95%)
- možnost černého rámečku
- čištění vodou variantně jemnou mýdlovou vodou

POUŽITÍ

Rolovací promítací plátna Rollo Standard do šíře 240 cm

PERFORMANCE

Base material :	woven fiberglass
Projection side :	matt white
Rear side :	black
Thickness :	0,35 mm
Weight :	450 g/m ²
Roll width :	320 cm
Weldable :	no
Washable :	yes
Fire resistance :	B2 acc. DIN 4102 part 1
Screen type :	D (diffuse)
Application :	front projection
Light proof :	>95%
Gain :	1,1
Viewing angle :	+/- 60°
High resolution compatibility :	2K

CHARACTERISTICS

- wide viewing angle, projected light is diffused in all directions
- accurate and natural color rendition
- lightproof back layer (>95%)
- black masking available
- clean with water, optionally with mild soap water

APPLICATION

Roll up projection screens Rollo Standard up to width 240 cm

FAKTOR JASU MĚŘEN DLE DIN 19045 | GAIN ACCORDING TO DIN 19045

